

ECOSHIELD™ METALLIC REPLACEMENT FILTERS

Model	Max Fixer Flow Rate	Incoming Silver Content (Grams per Liter)	Maximum Fixer Process Gallons/Liters	Maximum Recommended Recovery Period (Days)	Process	Dimensions
MR55 7111CA	60 ml/min	0.5 g/l 2.0 g/l 5.0 g/l 8.0 g/l	150/570 125/475 100/375 75/285	90	All Fixer Types	H x Dia: 15 x 12.5 in/38 x 32 cm Weight: 13 lbs/6 kg
MR65 7112CA	100 ml/min	0.5 g/l 2.0 g/l 5.0 g/l 8.0 g/l	300/1136 250/950 200/750 150/570	90	All Fixer Types	H x Dia: 19 x 12.5 in/48 x 32 cm Weight: 19 lbs/8.6 kg
MR95 7113CA	300 ml/min	0.5 g/l 2.0 g/l 5.0 g/l 8.0 g/l	900/3400 800/3000 350/1325 200/750	90	All Fixer Types	H x Dia: 22 x 17 in/56 x 43 cm Weight: 36 lbs/16.3 kg

Includes exclusive visual safety bypass to alert to clogged filters and prevent processor backup.
For best results, solution flow rate should be metered through filters.
It is recommended that two filters connected in series, be used to meet discharge limits.

MR200 AND REPLACEMENT CARTRIDGES

Model	Max Fixer Flow Rate	Incoming Silver Content (Grams per Liter)	Maximum Fixer Process Gallons/Liters	Maximum Recommended Recovery Period (Days)	Process	Dimensions
MR200 7123CA	60 ml/min	2.0 g/l 3.0 g/l 4.0 g/l 8.0 g/l	180/680 150/580 110/426 75/284	180	All Fixer Types	Treats up to 25 gal/95 L per month L x W x H: 19 x 13 x 15 in/48 x 33 x 38 cm Weight: 35 lbs/15.9 kg
Replacement Cartridge Set 7101AA				180	All Fixer Types	Two 4.6/1.8kg cores w/filter bags Weight: 10 lbs/4.5 kg

OTHER

Model	Features	Specifications	Dimensions
MS100 7122CA	Easy to install! Simple to calibrate. Fully Automatic Operation. Large funnel for manual pour. Connects easily to multiple processors. Adjustable pump rate (50 - 150 ml/min) 10-58 gal/day. Hour Meter determines volume of solution metered. Serves as a holding tank for processor maintenance. Oversize manual fill port for manual pouring and inspection. Reliable long lasting Bellows metering pump with EDPT seals.	115 V 60 Hz, 2 Amps Holding Capacity: 15 gal/57 L Daily Processing Capacity: 19 to 50 gal/72 to 189 L	H x Dia. 30.5 x 14 in/77 x 36 cm Weight: 19 lbs/8.6 kg
ESB 7103CA	Economically Priced. Inner vapor lid. Neutralizes pH. Never needs replacement. Rugged chemical resistant molded cabinet. Drain Valve for easy maintenance. Provides convenient sample point for silver testing. May be connected to two processors. Reduces B.O.D. and C. O. D. levels. Includes Wizard Rocks.	Holding Capacity: 5 gal/19 L 2.0 gal/min max.	L x W x H: 14.75 x 14.75 x 14 in/38 x 38 x 36 cm Weight: 20 lbs/9.09 kg